

GPOS OCBS-2017 1D/2D Barcode Scanner



Features:

- High Performance imaging technology
- Omni-directional scanning
- 4mil excellent scanning accuracy
- Multi special function setting supported
- High compatibility for all major 1D and 2D symbols
- Can read the barcode on the screen and color barcode

Product specifications are subject to change without prior notice.

Together We Quest For The Best

Specification

General	
Model	OCBS-2017
Color	Black
Material	ABS+PC
Processor	32-bit ARM MCU + DSP
Interface	USB; USB virtual COM; RS232
Prompt mode	Buzzer, indicator(LED)
IP grade	IP42
Power consumption	375mW(Working);226mW(standby);750mW(Max)
Power supply	DC 5V ±5%
OS support	Linux, Android, Windows XP、7、8、10, MAC
Performance	
Sensor	CMOS
Light source	Red LED(Aiming)+White LED(Lighting)
Resolution	≥4mil (PCS90%,CODE 39)
Error rate	1/5 million
Motion Tolerance	25cm/s
Reading Mode	Image
Trigger mode	Manual,Continuous scanning,Auto-sensing
ESD Protection	15KV air discharge
Shock resistance	1.5m free fall on concrete surface
Symbolic contrast	≥25%
Barcodes	1D:Code25-Interleaved , Code25-Standard , Code25-Matrix , Code39-Regular, Code39-FullASCII, Code32, Code93-Regular, Code93-FullASCII, Code128, EAN/GSL/UCC-128Auto ,Codabar,MSI ,EAN/JAN-13,UPC-A,JAN-8,UPCE 2D:PDF417, QR Code, Data Matrix
Reading depth	Code39 4.17mil(15bytes):4cm-8cm Code128 4.17mil(16bytes):7cm-15cm Data Matrix 10.83mil(8 bytes):3cm-9cm Code QR 10.83mil(8 bytes):7cm-12cm
Scanning Angle	Roll360°,Pitch30°,Yaw45°
Physical	
Weight	Net:320g Gross: 400g
Package box	195*105*80mm
30 in 1 carton	570*430*280mm/7.0kg

Product specifications are subject to change without prior notice.

Environment		
Working humidity	temperature&	0 to 45 degrees centigrade, 10%~80% No condensation
Storage humidity	temperature&	-20 to 60 degrees centigrade , 10%~90% No condensation

Product specifications are subject to change without prior notice.

Together We Quest For The Best