



WP260K

Thermal Receipt Printer

- Adopt brand-new calibration technology to avoid cutter jam
- Printer head life:150KM & Cutter life:1.5 million cuts
- Support IAP update online
- Wall mounted
- With printer head overheating protection function
- With sound and light alarm function
- Widely used in Supermarket, Catering, Storage, Hospital, Bank, Post



Supermarket



Medical Care



POST



Bank





WP260K

Thermal Receipt Printer



Printing WP260K	
Printing method	Direct thermal
Printer width	80mm
Column capacity	576 dots/line
Printing speed	260mm/s
Interface	USB+Serial+Lan
Printing paper	79.5±0.5mm x φ80mm
Line spacing	3.75mm(Adjustable by commands)
Print command	ESC/POS
Column number	80mm paper: Font A - 42 columns or 48 columns/ Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots Simplified/Traditional Chinese: 24x24 dots
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe)/Katakana/PC850(Multilingual)/PC860(Portuguese)/ PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/ Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)
1D code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D code	QR Code / PDF417
Buffer	
Input buffer	128 Kbytes
NV Flash	256Kbytes
Power	
Power adaptor	AC: 100-240V, 50~60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1.1 KG
Dimensions	188(D)×140(W)×137.7(H)mm
Environmental Requirements	
Work environment	Temperature (0~45℃) humidity(10~80%)(non-condensing)
Storage environment	Temperature(-10~60℃) humidity(10~90%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150KM
Driver	Win 9X / Win 2000 /Win 2003 /Win XP /Win 7 /Win 8 /Win 10/Linux

